



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: SILICONE SEALANT/ADHESIVE**

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Type:	Solvent Release Adhesive RTV	<b>Emergency Contact:</b>	<b>Chemtrec</b>
Product Name:	<b>SILICONE SEALANT/ADHESIVE</b>	<b>Phone:</b>	<b>(800) 424-9300</b>
<b>Part Number(s):</b>	<b>19-158</b> <b>19-159</b>		

### HMIS III RATINGS

**Health:** 1  
**Flammability:** 0  
**Physical Hazard:** 1

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

### SECTION 2. COMPOSITION

**Single or Mixture:** Mixture  
**Chemical Identification:** Organopolysiloxane mixture  
**Hazard Component(s)/(CAS NO.):** No hazardous materials present  
(See Section 8 of this MSDS for Exposure Guideline)

### SECTION 3. HAZARDS IDENTIFICATION

**Hazards Classification:** None (based on IMO)  
**Fire and Explosion** Not considered flammable nor combustible, but will burn if involved in a fire.

#### Potential Health Effect

**Inhalation:** Vapor overexposure may cause drowsiness, injure blood and liver, and may irritate eyes, nose and throat  
**Skin Contact:** On direct contact uncured product or its vapor may cause slight irritation to skin.  
**Eye Contact:** On direct contact uncured product or its vapor may cause slight irritation to eyes.  
**Ingestion:** No information is available

### SECTION 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air  
**Skin Contact:** Immediately remove product from skin with dry cloth or towel, and wash exposed area with detergent  
**Eye Contact:** Immediately flush with plenty of water for at least 15 minutes and promptly call a physician  
**Ingestion:** Wash out mouth with water provided person is conscious. Never give anything by mouth to an unconscious person.  
Call a physician immediately.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: SILICONE SEALANT/ADHESIVE**

### SECTION 5. FIRE FIGHTING MEASURES

**Flash Point (method used):** Not applicable (Solid)  
**Flammable Limits:** Lower: Not determined Upper: Not determined  
**Extinguishing Media:** Foam, dry chemical or carbon dioxide or fine water spray  
**Special Fire Fighting Procedure:** None  
**Unusual fire and explosion Hazard:** None

### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Steps to be taken in case material is released or spilled:**  
Shut off all ignition sources  
Contain the spill or leak.  
Scrape up with cardboard or rag and place in container.

### SECTION 7. HANDLING AND STORAGE

**Precaution to be taken in handling and storing:**  
Keep container closed when not in use.  
Store in a cool place.  
Keep away from heat, sparks and flame.  
Do not lay the container on its side.  
Use only with adequate ventilation  
Avoid contact with eyes and skin  
Keep out of reach of children.  
Contact lens wearers take appropriate precaution

\*\*\* Information about the emptied container \*\*\*

Do not re-use this container  
Keep away from heat, sparks and flame  
Do not puncture or cut this container, and do not weld on or near this container.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: SILICONE SEALANT/ADHESIVE**

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines:**

Vendor Guide; 3ppm (TWA), 10 ppm (STEL)  
AIHA WEEL\*; 10 ppm (TWA)

[Methylethylketoxime; decomposed product]

(\*AIHA WEEL = American Industrial Hygiene Association Workplace Environmental Exposure Level)

**Respiratory Protection (Specific Type):** Use air-supplied breathing apparatus unless local exhaust ventilation is adequate or decomposed product is within AIHA guideline

**Ventilation: Local Exhaust** Required

**Mechanical (general):** Adequate ventilation system

**Special:** Unknown

**Other:** Pay attention to ventilation such as local exhaust, mechanical and/or leave door open for at least 24 hours after application.

**Protective Gloves:** Plastic Film or rubber gloves

**Other Protective Clothing or Equipment:** Eyewash equipment

**Work/Hygienic Practices:** Wash hands after handling.  
Keep away from heat and flame  
Avoid Contact with eyes and prolonged or repeated skin contact.  
Avoid prolonged breathing vapor.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point:</b>	Not applicable
<b>Vapor Pressure:</b>	Negligible (25°C)
<b>Vapor Density (air=1):</b>	>1
<b>Specific Gravity:</b>	1.05 (25°C)
<b>Melting Point:</b>	Not applicable
<b>Evaporation Rate:</b>	<1 (Butyl Acetate=1)
<b>Solubility in Water:</b>	Not soluble
<b>Appearance (color)</b>	See Cartridge
<b>Appearance (form):</b>	Paste
<b>Odor:</b>	Oxime odor



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: SILICONE SEALANT/ADHESIVE**

### SECTION 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Condition to Avoid:** Exposure to air or moisture until ready to use - causes curing and methylethylketoxime vapor to form gradually

**Incompatibility (Material to Avoid):** Water or moisture

**Hazardous Decomposition or By-Product:** Water, moisture, or humid air can cause Methylethylketoxime Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon oxides and traces of incompletely burned carbon compounds. Silicone dioxide. Nitrogen oxides. Formaldehyde

**Hazardous Polymerization:** Will Not Occur

**Conditions to Avoid:** None

### SECTION 11. TOXICOLOGICAL INFORMATION

- Skin Irritation:** No information is available  
See OTHER INFORMATION
- Eye irritation:** No information is available  
See OTHER INFORMATION
- Sensitization:** No information is available  
See OTHER INFORMATION
- Acute Toxicity (LD50):** No information is available  
See OTHER INFORMATION
- Acute Toxicity (LC50)** No information is available  
See OTHER INFORMATION
- Subacute Toxicity:** No information is available  
See OTHER INFORMATION
- Chronic Toxicity:** No information is available.  
See OTHER INFORMATION
- Carcinogen:** NTP: Not Listed IARC: Not Listed: OSHA Regulated: Not Listed  
See OTHER INFORMATION
- Mutagenicity:** No information is available  
See OTHER INFORMATION
- Other Information:** **Additional Information**  
Methyl Ethyl Ketoxime (MEKO) — Decomposition product  
Material will generate MEKO on exposure to humid air, gradually. Male rodents exposed to MEKO vapor at high concentration throughout their lifetime developed liver cancer. But relevance to humans is uncertain now. Please read the detail information to MEKO below.  
Causes mild irritation. Can be absorbed through the skin
- Skin Irritation:** Causes severe irritation
- Eye Irritation:** LD50 (rat) = 4ml/kg.
- Acute Oral Tox:** LC50 (rat) = >4.8 mg/l /4HR
- Acute Inhalation Tox:** Shows narcotic action at high concentration. May produce blood effects
- Inhalation Tox:** Positive (guinea pig)
- Skin Sensitization:** High dose can product transient and reversible change in neurobehavioral function. No evidence of cumulative neurotoxicity was detected.
- Neurotoxicity:**
- Carcinogenicity:** Liver carcinomas were observed in a lifetime inhalation study (ca.2 years) in which mice and rats were exposed. These carcinomas were statistically increased in males at concentration of 735 ppm. Relevance to humans is uncertain now MEKO



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

### MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

#### Product Name: SILICONE SEALANT/ADHESIVE

#### SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

**Mutagenicity:** Not considered mutagenic based on several in vitro and vivo studies.  
**Other Chronic Study:** Degenerative effects on the olfactory epithelium of nasal passages occurred in a concentration related manner in males and females of mice and rats at MEKO concentration of 15,75 and 375 ppm.  
**Workplace Environmental Exposure:** Exposure Level AIHA WEEL: 10 ppm (TWA)

#### SECTION 12. ECOLOGICAL INFORMATION

**Biodegradation:** Not applicable  
**Bioaccumulation:** No information is available  
**Aquatic Toxicity:** No information is available  
**Other Information:** None

#### SECTION 13. DISPOSAL CONSIDERATION

Can be land-filled for cured product or burned in a chemical incinerator equipped with an afterburners and scrubber  
Do not dispose the emptied container unlawfully.  
Observe all federal, state, and local laws.

#### SECTION 14. TRANSPORTATION INFORMATION

**US DOT & CANADA TDG SURFACE**  
Valuation.....: Not regulated for transport  
**Transport by sea IMDG-Code**  
Valuation.....: Not regulated for transport  
**Air transport ICAO-TI/IATA-DGR**  
Valuation.....: Not regulated for transport



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 275  
Revision Date: 01/29/2013  
Supersedes Date: 02/19/2010

**MATERIAL SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: SILICONE SEALANT/ADHESIVE**

**SECTION 15. REGULATORY INFORMATION**

**Toxic Substances Control Act (TSCA) Status:** Listed on the TSCA inventory  
\*\*\*\*\*

**European Inventory Of Existing Commercial Chemical Substances (EINECS) Status:**  
Listed on the EINECS

**Labeling According To EC-Regulations Required:**  
Symbol: Not required  
R-Phrase: Not required  
S-Phrase: Not required  
Contains: None

Superfund Amendments and reauthorization to of 1986 (SARA) Title III Section 313 Supplier Notification:  
This regulation required submission of annual reports of toxic chemical(s) that appear in section 313 of the emergency planning and community Right-To-Know Act of 1986 and 40 CFR 372. This information must be included in all MSDS's that are the toxic chemical(s) contained in this product are:

**Chemical Name(CAS No.) And Contents:** None  
\*\*\*\*\*

**California Proposition 65:**  
This regulation requires a warning for California Proposition 65 Chemical(s) under the stature.

**The California Proposition 65 Chemical(s) contained in this product are:**  
**Chemical Name/(CAS No.) And Contents:** None

**SECTION 16. DISCLAIMER**

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.